

- Single chamber
- 10,1" touchscreen display
- 100% closed loop circuit
- 2 Tanks, 3 Pumps
- 2 horizontal CSR (Cepter Spray Rotor)
- o Coarse filter inside process chamber, Sediment filter inside fluid tanks
- Fine 10" filter in each circuit
- o 2 Air heaters with high air volume blower
- Electric safety door lock
- Fluid leakage tray in stainless steel
- Status light
- Complete machine body in stainless steel
- Cleaning fluid heater, rinsing 1 fluid heather
- Conductivity measurment rinse circuit
- Cartridge for deionized and demineralized water
- Active Carbon filter

Optional equipment

- 3 Tanks, 4 Pumps
- Rinsing 2 fluid heater
- MixAssist system easy & accurate mixing water with cleaning agent
- Special carrier trolley upon customer request
- Leakage warning system

| Technical data | |
|-------------------------------|--|
| Dimensions | W 1.100 mm x D 1.600 mm x H 1.800 mm |
| Chamber dimensions | W 700 mm x D 750 mm x H 850 mm |
| Usable space in mm (WxDxH) | Lower basket 630x700x300, Upper basket 630x700x290 |
| Volume cleaning tank | 651 |
| Volume rinsing tank 1,2 | 65 I, 35 I |
| Exhaust connection | Ø 100 mm |
| Power supply | 400 V AC, 25A / 3 Ph / 50 Hz |
| Power consumption | ca. 4,7 kW |
| Control system | 10,1" touchscreen |
| Conductivity range | 0-300 μS |
| Temperature range cleaning | adjustable up to 65°C |
| Temperature range rinsing 1,2 | adjustable up to 40°C |
| Temperature range drying | up to 90°C |
| Filter system | 3-stage: 1.Main filter <2 mm; 2.Coarse filter (inside fluid tank); 3.Fine filter 10" 5–200 μm) |
| Noise level | < 70 dB |
| Weight | 550 kg |

* Product availability, apperance, technical specifications and details are subjected to continuous development. As such, we accept no liability for errors,

Slovenia

CEPTER d.o.o GSM: +386 41 344 535 Polje 9, 6310 Izola Email: info@cepter.si www.cepter.si



Authorized distributor:



PRECISION CLEANING Elektron 360-HC

Fully automatic single chamber cleaning system for:

- -PCBs.
- -DCBs,
- -Hybrids,
- -SDIs,
- -SIPs, **Misprints**

Other models: **ELEKTRON 170 ULTRA II ELEKTRON 250-HC ELEKTRON 400-VC**



