## **PRODUCT BULLETIN**



# **KYZEN® E5611** Stencil and Misprinted Board Cleaner

KYZEN<sup>®</sup> E5611 is a cost effective cleaning chemistry designed to be diluted for removing flux, solder paste and uncured adhesives from stencils and misprints. E5611 has proven compatible with most standard stencil cleaning equipment.



- Works Great at Ambient Temperature
- Designed for Spray-in-Air and Ultrasonic Systems
- Successful at Cleaning Raw Paste and Uncured Adhesives in Stencil Applications
- Effective at Low Concentrations
- Compatible with Standard Stencil Cleaning Equipment

| PRODUCT PROPERTIES |                    |
|--------------------|--------------------|
| pH (10g/L)         | Neutral            |
| FLASH POINT        | None to Boiling    |
| BOILING POINT      | 219°F / 103°C      |
| WATER SOLUBLE      | Partially Miscible |
| VOC, @ 10%         | 82.2 g/L           |

| TYPICAL PROCESSES |                      |
|-------------------|----------------------|
| APPLICATION       | Spray & Ultrasonic   |
| CONCENTRATION     | <25%                 |
| TEMPERATURE       | 120°F / 49°C         |
| RINSE             | Recommended DI Water |
| DRY               | Hot Air              |

The above process parameters are recommendations based on extensive testing done in KYZEN's Application Lab. Your KYZEN Sales Representative can assist you in optimizing your process parameters.

#### STORAGE AND HANDLING

- Packaged in Polyethylene Containers
- Store at 5-30°C/41-86°F in Original Container
- Standard Chemical Handling Practices
- Shelf Life of 5 Years, in Sealed Containers of 5 gallons / 25 liters or more

### AVAILABILITY

- 1 Gallon
- 25 Liters\*
- 5 Gallons 55 Gallons
- 200 Liters\*

• 5 Liters\*

\* Liters Available in South Asia and Europe





## ENVIRONMENTAL, HEALTH AND SAFETY REGULATIONS

KYZEN® E5611 is a non-hazardous, biodegradable aqueous solution. It contains no CFC's or HAP's. Refer to the Material Safety Data Sheet for more information.



## COMPATIBILITY

**REACH V** KYZEN is an ISO 9001:2008 company.

KYZEN® E5611 is compatible with all materials commonly used in electronic assembly manufacturing and cleaning processes. For specific compatibility information, please contact your KYZEN representative.



## FREE CLEANING TRIALS AND PROCESS OPTIMIZATIONS

KYZEN will conduct complimentary trials at your factory or "risk-free" testing in one of our global Applications Laboratories in North America, Asia or Europe to ensure you achieve your goal. Increase your yields and product reliability by identifying and tuning the critical parameters of your cleaning process. With our commitment to science and understanding process, KYZEN has the flexibility to simulate and refine any cleaning process – including vours!

Each laboratory is fully equipped with an extensive array of cleaning and analytical equipment, including, but not limited to:

- Batch Washers • In-Line Washers
- Scanning Electron Microscope (SEM)
- Ultrasonic Systems
- SUI Systems
- Vapor Degreasers
- GC (TCD and FID)
- Ion Chromatography
- FTIR Spectrophotometer
- Humidity Chamber
- High Powered Microscopes





#### Aqueous, Semi-Aqueous and Vapor Phase Chemistries • Process Evaluation and Optimization Contract Cleaning • Cleanliness Testing • Soil Analysis

## **KYZEN.com**

Penang, Malaysia SOUTHEAST ASIAN HEADQUARTERS +60 4 630 3000

Maldegem, Belgium EUROPEAN HEADQUARTERS +32 50 395 374

Nashville, TN GLOBAL HEADQUARTERS (615) 831-0888

Manchester, NH NORTH AMERICAN OPERATIONS FACILITY (603) 622-2900

The information contained herein is based on available data from reliable sources and is accurate to the best of KYZEN Corporation's knowledge at the time of this publication. The user is solely responsible for determining the suitability and completeness of such information for their particular application and for adopting appropriate safety precautions. This data is not to be taken as a warranty or representation for which KYZEN assumes legal or financial responsibility. 071315