

CUVE A ULTRA-SON

Features:

- Die casting SUS304 stainless steel tank
- Industrial grade integrated circuit
- 0~80 °C temperature range
- 1~99 minutes working time
- Power sweep to prevent ultrasonic fatigue
- Dewaxing and degreasing function
- Auto Stand-by, Sleep, and wake up by one key-press Mode
- Digital controller of high-precision and a long service-life
- Fullwave(40KHz) for intensive rinse, semiwave(33KHz) for gross rinse



Application:

Smart dual frequency ultrasonic cleaners are suitable to clean irregular and complex specialized instruments, components and PCBs of sundry shops, workshops, factories, etc; smash, emulsify, scatter, hydrolyze, extract, degas certain analyzed stuffs in labs.

Specifications:

Model No.	Tank Size (mm)	Overall Size (mm)	Capacity (L)	Frequency (KHz)	Ultrasonic Power (W)	Heating Power (W)	Timing (min: secs)	Temp. (°C)	Drainage
DK-300PF	240*140*100	270*170*240	3.2	33,40	120	100	1~99	0~80 °C	Yes
DK-400PF	300*155*100	312*162*240	4.5	33,40	120	100	1~99	0~80 °C	Yes
DK-450PF	300*155*100	312*162*240	4.5	33,40	180	100	1~99	0~80 °C	Yes
DK-600PF	300*155*150	330*180*330	6.5	33,40	180	300	1~99	0~80 °C	Yes
DK-1000PF	300*240*150	330*270*330	10	33,40	240	300	1~99	0~80 °C	Yes
DK-1400PF	300*240*200	330*270*380	14	33,40	300	400	1~99	0~80 °C	Yes
DK-1500PF	330*300*150	360*330*330	15	33,40	360	400	1~99	0~80 °C	Yes
DK-1900PF	330*300*200	360*330*380	19	33,40	480	500	1~99	0~80 °C	Yes
DK-2200PF	500*300*150	550*330*330	22	33,40	480	500	1~99	0~80 °C	Yes
DK-3000PF	500*300*200	550*330*380	30	33,40	600	500	1~99	0~80 °C	Yes